

HDb2500 Series

Scalable 720p Encoder/ RF Modulator



For organizations looking for cost-effective HD encoding the HDBridge 2500 Series is the perfect fit. Choose from two or four channels models that allow you to deliver HD video up to 720p resolution to an unlimited number of displays over almost any distance.

The HDBridge 2500 series converts high definition AV sources into an RF signal received a television's QAM (NA model) or DVB-T/C (EU model) digital tuner over coax cable. With its high 45 dBmV RF output, you can send your content to an unlimited number of displays over nearly any distance.

Multiple units can be combined to create a headend that supports over 100 channels on the RF network. This unit is designed primarily for high channel density environments where rapid deployment, advanced management, and compatibility are critical.

MODELS:

HDb2520-EU:

2 DIN inputs for up to 720p component/VGA video

HDb2540-EU

4 DIN inputs for up to 720p component/VGA video

Superior Video Quality

- Full MPEG-2 implementation
- I, P, and B Frames
- Low latency
- Full motion estimation with a wide search range

Extensible Architecture

- Easy downloadable firmware updates
- Future enhancements provided regularly
- Emergency Alert System (EAS)

High Reliability

- Low-stress power system
- Full system instrumentation and monitoring
- Official international regulatory approval
- Forced air cooling for effective thermal control

Ease of Management

- Powerful, highly intuitive web interface
- On-site or remote management
- Configure/manage multiple units from
- Front Panel Display for local management

HDb2500 Series Web-based Administration Interface

System	Slot	AV Port	Enabled	RF #	Channel #	Name	Long Name	Rating
4_support_4	1	zvshow	Enabled	38	38.1	2840-1	2840-1	TV-G
	2		Enabled	38	38.2	2840-sh	2840-show	TV-G
	3		Enabled	39	39.1	2840-2	2840-2	TV-G
	4		Enabled	40	40.1	2840-3	2840-3	TV-G
			Enabled	41	41.1	BBCAHD	Planet Earth	TV-G

General		
Power: 100-240 VAC 50/60 Hz, 60W max. 30W Typical IEC 60320-C14	Cooling: Dual internal cooling fans, Front inlet, Rear exhaust	Temperature/Humidity: Operating 0 C ^o to +45 C ^o (+32 F ^o to +113 F ^o) / 10% to 80%, non-condensing
	MBTF: 62,000 hours	Enclosure Type: Metal
Compliance: FCC Class A, IEC60065, EN61000 (see manual 70-00031-00), CE, RoHS, RCM C-Tick	Enclosure Dimensions: 43.6 mm (H) x 440.2 mm (W) x 251.5 mm (D) 1.72 in. (H) x 17.33 in. (W) (without rack mount ears) x 9.9 in. (D)	System Weight: 2.84 kg (6.25 lbs.)
		Shipping Weight: 3.58 kg (7.88 lbs.)
Mounting: Rack ears shipped attached, 1RU high	Carton Dimensions (individual): 108 mm (H) 785 (mm) W 308 (mm) (D) 4.25 in. (H) 30.875 in. W 12.125 in (D)	Warranty: 5 Years
		Vibration: NSTA 1A in carton
Input		
Component Video x4 or x2: DIN connector HDbridge end, RCA connectors for HD source up to 720p	VGA Resolutions Supported: 640x480, 720x480, 800x600, 1024x768, 1152x864, 1176x664, 1280x720, 1280x768, 1280x800, 1280x960, 1280x1024, 1360x768, 1440x900 at 60 70, 72, 75, 85 Hz.	Closed Caption: EIA/CEA-608 captions accepted over composite video input
Computer VGA (Analog) x4 or x2: HD-15 connector, 75 Ohm RGB 0 to 0.7V, Separate H and V sync		Extra Digital Channel: MPEG2 Program stream file, up to 200 MB
Stereo Analog and Digital Audio x4 or x2	Line level input per channel DIN connector HDbridge end, RCA connector or digital SPDIF audio input. 3.5 mm pigtail connector with VGA	
Video Encoder		
Encoder Video Profile: MPEG2 HD: ISO13818-2 MainProfile@ HighLevel	Traffic Shaping: Variable Bit Rate	Video Encoding Data Rates: Variable, 10 Mbs - 24 Mbs per channel
Average Encoding Data Rate: 18 Mbs per channel	Encoding Latency: Programmable 200 msec to 400 msec	Color Profile: 4:2:0
Encoder Audio Profile: ATSC A/52, (AC-3)	Video, Audio PID: Programmable starting value	Program Information: Programmable program name, EIT
GOP Size: 16		
Modulator/Upverter		
Modulation Types: DVB-T, DVB-C (ITU-T J83 Annex A) (varies by region)	Cable Standard: User defined (varies by region), CCIR	Frequency Range: Up to 4 paired frequency-agile CCIR Channels 21-79, 57 MHz - 900 MHz <ul style="list-style-type: none"> • 2 kHz resolution • +/- 30 ppm accuracy • +/- 35 ppm stability
Output Power: +45 dBmV typical	Output Level Adjust: 25 - 45 dBmV in 1dBmV steps	
I/Q Amplitude Imbalance: < 1% typical	Spectral Tilt: < /= 1 dB over 6 MHz typical	MER : > 38 dB typical
Control Setup		
Network Interface	10/100 Mb Ethernet via RJ45 connection IP address via DHCP or set by user HTML/Javascript served web interface for easy configuration Telnet connection for CLI scripting Easy firmware updates All settings saved in NV storage	
Front Panel Color Display	Quickly obtain status at a glance, basic configurations, software revisions and updates	

ZeeVee, Inc., headquartered in Littleton, Mass., and founded in 2007, is a leading global developer of digital technology and products for distributing audio-video content from any source or multiple sources to any number of displays. Manufactured in the U.S. and used primarily in commercial and corporate applications, ZeeVee products are employed worldwide by major organizations in education, government, hospitality, retail, sports, entertainment, broadcasting, healthcare, housing, energy and other industries. For more information visit www.zeevee.com