

ZyPer4K-XS

Product Number: Z4KENCC3XS

Uncompressed 4K Encoder

Z4KENCC3XS HDMI 2.0 input Encoder, with IP streaming via 10Gbit/copper. PoE. Supports HDMI and analog audio input. USB supported with between ZyPer4K XS/XR devices. Includes power supply. Compatible with any ZyPer4K Decoder. Cables not included.

Z4KENCC3XS



10Gb PoE
Ethernet
port

1 Gb
Utility
port

USB
port

Audio
Input

HDMI 2.0
Input

What's in the box?

- ZyPer4K-XS Encoder Copper
- Power Supply

ZyPer4K-XS

Product Number: Z4KENCC3XS

ZyPer4K-XS Encoder	Information												
Video	HDMI 2.0 with HDCP pass-through												
Audio (Digital)	Encoded audio formats and linear PCM up to 8 channels												
Audio (Analog)	Unbalanced Stereo (Output)												
USB	Single Mini USB 2.0 Type B port												
Ethernet	10 Gb for Video/Audio/Control with 1 Gb Utility												
Other Specifications	ZyPer4K-XS Encoder Copper												
Formats	<p>Supports all major VESA resolutions and variations including full HDMI 2.0 support:</p> <table border="0"> <tr> <td>VGA: 640x480 (4:3)</td> <td>XGA: 1024x768 (4:3)</td> </tr> <tr> <td>SXGA: 1280x1024 (5:4)</td> <td>SXGA+: 1440x1080 (4:3)</td> </tr> <tr> <td>1080p/i: 1920x1080 (16:9)</td> <td>Ultra HD: 3840x2160 (16:9)</td> </tr> <tr> <td>SVGA: 800x600 (4:3)</td> <td>HDTV: 1280x720 (16:9)</td> </tr> <tr> <td>WXGA: 1366x768 (16:9)</td> <td>UXGA: 1600x1200 (4:3)</td> </tr> <tr> <td>QXGA: 2048x1536 (4:3)</td> <td>4K: 4096x2160 (17:9)</td> </tr> </table> <p>Custom resolutions are supported at pixel clock rates up to 600 MHz</p>	VGA: 640x480 (4:3)	XGA: 1024x768 (4:3)	SXGA: 1280x1024 (5:4)	SXGA+: 1440x1080 (4:3)	1080p/i: 1920x1080 (16:9)	Ultra HD: 3840x2160 (16:9)	SVGA: 800x600 (4:3)	HDTV: 1280x720 (16:9)	WXGA: 1366x768 (16:9)	UXGA: 1600x1200 (4:3)	QXGA: 2048x1536 (4:3)	4K: 4096x2160 (17:9)
VGA: 640x480 (4:3)	XGA: 1024x768 (4:3)												
SXGA: 1280x1024 (5:4)	SXGA+: 1440x1080 (4:3)												
1080p/i: 1920x1080 (16:9)	Ultra HD: 3840x2160 (16:9)												
SVGA: 800x600 (4:3)	HDTV: 1280x720 (16:9)												
WXGA: 1366x768 (16:9)	UXGA: 1600x1200 (4:3)												
QXGA: 2048x1536 (4:3)	4K: 4096x2160 (17:9)												
Video Other	Color depth: 24 bit, 30 bit, 36 bit, 48 bit												
Video Wall and Multiview	Video Wall up to 15x15. Multiview with up to 19 sources												
Signal transmission distance	Cat6a: 100m												
Copy Protection/Security	HDCP 2.2, AES-128 Encryption, 802.1X compatible												
Power input (locking connector)	12V DC												
Power	Approximately 8 watts												
Dimensions (L x W x H) / Weight	7.8 in (199mm) x 4.6 in (116mm) x 1.9 in (47mm), 30.0 oz (850g)												
Temperature	Operating temperature: 32 F to 104 F <0 C to +40 C> Storage temperature: -4 F to +176 F <-20 C to +80 C>												
Humidity	Operating/ Storage: 20% to 90% (Non-Condensing)												
Accessories	Description												
Z4KPWRCTR12	ZyPer 12V Power Center for use with up to 8 ZyPer Encoder/Decoders (all models). 1 RU. Includes rack ears, 8 3-foot locking 12V DC power cables, AC power cord.												
Z4KRACKXS	ZyPer4K-XS Rack Mount Kit. Holds up to 8 ZyPer4K-XS Encoders/Decoders in standard 6RU space. Includes rack assembly and 8 carrier units.												
Z4KXSBP	ZyPer4K-XS Rack Mount Filler Plate Standard is used to cover unused slots in a ZyPer4K-XS Rack Mount Kit.												
Z4KVESABRK	ZyPer4K VESA Bracket is a custom wall/desk/display mount bracket for ZyPer4K. Supports standard VESA parameters for mounting directly to rear of a display. 100x100, 100x200 and 200x200 VESA hole mounts are supported.												

ENTIRE PRODUCT LINE:

Z4KDECC3XS
Z4KDECF3XS
Z4KENCC3XS
Z4KENCF3XS

Z4KC2XS-E
Z4KC2XS-EAU
Z4KF2XS-E
Z4KF2XS-EAU

Z4KC2XS-D
Z4KC2XS-DAU
Z4KF2XS-D
Z4KF2XS-DAU

ZYPER4K-XS WALL PLATES:

Z4KDECC3XS-WPEU-I
Z4KDECC3XS-WPEU
Z4KENCC3XS-WPUS-I
Z4KENCC3XS-WPUS